

Remington® Rem® Oil Pro<sup>3</sup>™

---

**1. PRODUCT AND COMPANY IDENTIFICATION**

---

**Product Name:** Remington® Rem® Oil Pro<sup>3</sup>™  
**Recommended Use:** Firearm Lubricant (not for incidental food contact or medical purposes)  
**Distributor:** Ammunition Operations LLC  
2592 AR Hwy 15N  
Lonoke, AR 72086, USA  
**Telephone:** 1-800-243-9700  
**Emergency Telephone:** 1-800-424-9300 (CHEMTREC, 24 hours, Washington, D.C. USA)

---

**2. HAZARDS IDENTIFICATION**

---

**Classification:** This mixture is considered moderately hazardous.

**Labeling:** Can cause eye and skin irritation. Category 2

**Symbol:**



Signal Word: Warning

Hazard statements:

May be harmful if swallowed

May cause eye irritation

May cause skin irritation

Non-flammable or combustible but may burn if involved in a fire. At extreme elevated temperatures HF, perfluoroisobutylene, perflourinated acid fluorides and other toxic vapors can be generated.

Wash hands thoroughly before using tobacco or other products intended to be burned and inhaled.

**Precautionary Statements:**

Use personal protective equipment as required. Wear safety glasses and gloves.

---

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

**Chemical Identity:** Phosphorodithioic acid, O, O-di-C1-14-alkyl esters, zinc salts; 0.5 – 1.5%  
**Common Name:** Zinc Alkyl Dithiophosphate  
**CAS Number:** 68649-42-3  
**Impurities:** No information provided by manufacturer

---

**4. FIRST AID MEASURES**

---

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Obtain medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

**Ingestion:** If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

---

**5. FIRE FIGHTING MEASURES**

---

**Autoignition Temperature:** >150°C  
**Flash point:** >150°C  
**Flammable Limits (LEL)** Not determined  
**Flammable Limits (UEL)** Not determined  
**Suitable Extinguishing Media:** On large fires used dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical, or water spray. Water

---

can be used to cool fire exposed containers.

**Unsuitable Extinguishing Media:** None.

**Specific hazards in case of fire:** Decomposes on heating and produces incompletely burned carbon compounds. Avoid reaction with oxidizers. At extreme elevated temperatures HF, perfluoroisobutylene, perfluorinated acid fluorides and other toxic vapors can be generated. Hydrogen Fluoride has an ACGH TLV of 3 ppm as fluoride as a Ceiling Limit and an OSHA PEL of 3ppm of fluoride as an eight-hour TWA and 6 ppm as a Short Term Exposure Limit. The odor threshold for HF is 0.04 ppm, providing good warning properties for exposure.

**Special protective equipment and precautions for fire fighters:**

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self-contained breathing apparatus with a full-face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions:** Use appropriate personal protection. (See section 8.)

**Environmental precautions:** For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**Methods for material containment and cleaning up:** Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated. Wash hands thoroughly before using tobacco or other products intended to be burned and inhaled.

**Conditions for safe storage, including any incompatibilities:** Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Control Parameters:** Under most handling conditions, this product will not generate mist or dust.

**Engineering Controls:** In most conditions, no special local ventilation is needed. General ventilation recommended. If the product is atomized ventilation should be used.

**Personal Protective Equipment (PPE):**

**Eyes:** Safety glasses recommended.

**Skin:** Impermeable gloves should be worn. Petroleum resistant elastomers are recommended.

**Inhalation:** No respiratory protection required under most conditions. If concentrations exceed exposure limits, approved respiratory equipment must be used.

---

## 9. CHEMICAL AND PHYSICAL PROPERTIES

---

**Physical state:**..... Liquid

**Color:**..... Amber

**Odor:** ..... Mild petroleum

Remington® Rem® Oil Pro<sup>3</sup>™

**Odor Threshold:** ..... Not available  
**pH Value:**..... Not applicable  
**Melting Point:** ..... -30°C  
**Freezing Point:** ..... Becomes very stiff with decreasing temperature around -50°C  
**Initial Boiling Point:** ..... >150°C  
**Flash Point:**..... >150°C COC  
**Evaporation rate:** ..... Not available  
**Flammability (solid, gas):**..... Not applicable  
**Explosion limits:** ..... Not available  
**Vapor pressure:** ..... Negligible at 20°C  
**Vapor density:** ..... Not available  
**Solubility:**..... Insoluble in water at 20°C  
**Partition coefficient:** ..... Not available  
**Auto-ignition temperature:**..... Not available  
**Decomposition temperature:** ..... Begins to oxidize at a slow rate at 125°C

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under ambient temperatures and pressures  
**Possibility of hazardous reactions:** Can react with strong oxidizers. Other hazardous reactions have not been identified. Otherwise will not react or polymerize.  
**Conditions to avoid:** No specific conditions to avoid have been identified.  
**Materials to avoid:** Oxidizers.  
**Hazardous decomposition products:** Decomposes on heating and produces incompletely burned carbon compounds. At extreme elevated temperatures HF, perfluoroisobutylene, perfluorinated acid fluorides and other toxic vapors can be generated. Hydrogen Fluoride has an ACGH TLV of 3 ppm as fluoride as a Ceiling Limit and a OSHA PEL of 3ppm of fluoride as an eight hour TWA and 6 ppm as a Short Term Exposure Limit. The odor threshold for HF is 0.04 ppm, providing good warning properties for exposure.

## 11. TOXICOLOGICAL INFORMATION

General information Not available. Information on likely routes of exposure  
 Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.  
 Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for classification.  
 Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.  
 Eye contact May be irritating to eyes. Symptoms Not available.  
 Information on toxicological effects  
 Acute toxicity Not classified.  
 Skin corrosion/irritation Not classified. May cause defatting of the skin but is neither an irritant nor a sensitizer.  
 Respiratory sensitisation Not classified. Skin sensitisation Not classified.  
 Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.  
 Carcinogenicity Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.  
 Reproductive toxicity Contains no ingredient listed as toxic to reproduction  
 Aspiration hazard Not classified.  
 Mixture versus substance information: Not available  
 Other information Not available.

## 12. ECOLOGICAL INFORMATION

Toxicity Not expected to be harmful to aquatic organisms. Persistence and degradability: Not inherently biodegradable.

**Remington® Rem® Oil Pro<sup>3</sup>™**

Bioaccumulative potential: Bioaccumulation is unlikely to be significant because of the low water solubility of this product.  
 Partition coefficient n-octanol/water (log Kow): Not established. Bioconcentration factor (BCF): Not available.  
 Mobility in soil: Not available.  
 Results of PBT and vPvB assessment: Not applicable.  
 Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. DISPOSAL PROCEDURES**

**Waste treatment methods:** Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible or dispose of in an authorized landfill.  
**According to the European Waste Catalogue,** Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.  
**For USA Disposal:** Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

**14. TRANSPORT INFORMATION**

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

**15. REGULATORY INFORMATION**

**Safety, health, and environmental regulations/legislation specific for the mixture: Other Information:**

**U. S. Regulatory information**

TSCA Inventory Status: ..... Y  
 TSCA 12 (b) Export Notification:..... Not listed  
 CERCLA Section 103 (40 CFR 302.4): ..... N  
 SARA Section 302 (40 CFR 355.30): ..... N  
 SARA Section 304 (40 CFR 355.40): ..... N  
 SARA Section 313 (40 CFR 372.65): ..... Zinc compounds, < 2%  
 OSHA Process Safety (29 CFR 1910.119):..... N  
 SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) –  
     Acute Hazard: ..... N  
     Chronic Hazard: ..... N  
     Fire Hazard: ..... N  
     Reactivity Hazard: ..... N  
     Sudden Release Hazard: ..... N

**State Regulations:** Not on California Proposition 65 list. Does not contain any contaminants or by-products known to the State of California to cause cancer or reproductive toxicity.

**Note –** There are no known safety, health, or environmental restrictions or prohibitions in any country where this product is produced, imported, or marketed.

**Chemical Inventories:**

DSL (Canada)	All ingredients listed or exempt EINECS (European Union)
TSCA (United States of America)	All ingredients listed or exempt ENCS/ISHL (Japan) All ingredients listed or exempt IECSC (Peoples Republic of China) All ingredients listed or exempt

**16. OTHER INFORMATION**

NFPA Hazard Classification: Health: 1  
 Flammability: 1  
 Reactivity: 0

**Remington® Rem® Oil Pro<sup>3</sup>™**

Special Hazards:           None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification: Health: 1

Flammability:           1

Reactivity:               0

Protection:            B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Prepared By:                           PolySi® Technologies, Inc.  
5108 Rex McLeod Dr. Sanford N.C. 27330  
Email polysi@polysi.com  
Phone: (919) 775-4989